

BULLETPROOF

Bullet resistant glazing is designed to give occupants and first responders the precious minutes they need to seek safety or to arrive on the scene.

The shelling test in accordance with the European standard EN 1063 is only the beginning. In addition, we test our Bullet resistant glass with totally different weapons. For example, with Kalashnikov AK 47 and standard ammunition. But also with war weapons - loaded with hard-core bullets or special incendiary devices like the M107A1-.50-BMG. We have test certificates in accordance with the UL752 standard for this weapon.



BR 2
9mm



BR 3
Mag.357



BR 4
Mag.44



BR 5
5.56 x 45



BR 6 / BR 7
7.62 x 51



SG 1 / SG 2
12/70

SPALLING

EN STANDRAD	CLASS	PROTECTION	TYPE	THICKNESS mm	WEIGHT kg
EN 1063	BR2-S	SPALLING	ASPISLAM BR2206-S	21	44,8
EN 1063	BR3-S	SPALLING	ASPISLAM BR3231-S	23	53,2
EN 1063	BR4-S	SPALLING	ASPISLAM BR4328-S	33	76,5
EN 1063	BR5-S	SPALLING	ASPISLAM BR5368-S	37	86,5
EN 1063	BR6-S	SPALLING	ASPISLAM BR6503-S	50	118,1
EN 1063	BR6-S	SPALLING	ASPISLAM BR6681-S	66	161,4
EN 1063	BR7-S	SPALLING	ASPISLAM BR7681-S	76	156,4
EN 1063	SG1-S	SPALLING	ASPISLAM SG1328-S	33	81,5
EN 1063	SG2-S	SPALLING	ASPISLAM SG2507-S	51	112,3
EN 356 + EN 1063	P6B BR2-S	SPALLING	ASPISLAM PBR62.206-S	15	44,8
EN 356 + EN 1063	P8B BR3-S	SPALLING	ASPISLAM PBR83.298-S	30	69
EN 356 + EN 1063	P7B BR3-S	SPALLING	ASPISLAM PBR73.238-S	24	54
EN 356 + EN 1063	P8B BR5-S	SPALLING	ASPISLAM PBR85.368-S	37	86,5
EN 356 + EN 1063	P8B	SPALLING	ASPISLAM EXTREME PBR84.213-NS	21	45,65

NON SPALLING

EN STANDRAD	CLASS	PROTECTION	TYPE	THICKNESS mm	WEIGHT kg
EN 1063	BR2-NS	NON SPALLING	ASPISLAM BR2310-NS	31	63,2
EN 1063	BR3-NS	NON SPALLING	ASPISLAM BR3444-NS	44	106,1
EN 1063	BR4-NS	NON SPALLING	ASPISLAM BR4538-NS	53,8	128,6
EN 1063	BR5-NS	NON SPALLING	ASPISLAM BR5586-NS	59	139,8
EN 1063	BR6-NS	NON SPALLING	ASPISLAM BR63726-NS	73	174,8
EN 1063	BR7-NS	NON SPALLING	ASPISLAM BR7887-NS	88	206,2
EN 1063	BR3-NS	NON SPALLING	ASPISLAM EXTREME BR3213-NS	21	48,15
EN 1063	BR4-NS	NON SPALLING	ASPISLAM EXTREME BR4248-NS	24	50,65
EN 1063	BR5-NS	NON SPALLING	ASPISLAM EXTREME BR5320-NS	32	71,45
EN 1063	BR6-NS	NON SPALLING	ASPISLAM EXTREME BR6388-NS	39,3	84
EN 1063	BR7-NS	NON SPALLING	ASPISLAM EXTREME BR7712-NS	71	156,6